



High Performance Paint Product Data Sheet



EVO ACRYLIC LOW SHEEN

01-225 JUN 09



DESCRIPTION: General purpose interior acrylic low sheen paint. Can be used in limited exterior applications, such as protected soffits.

TYPICAL USES: Interior surfaces e.g. walls, ceilings, gib board, etc. Not recommended for wet areas such as bathrooms and kitchens. Exterior uses; eaves, barge boards.

PERFORMANCE: High quality interior acrylic low sheen with excellent wear ability.

LIMITATIONS: Not recommended for kitchens, bathrooms, i.e. wet areas. Not for use on new concrete or timber surfaces. Do not apply if the air and surface temperature during application and drying is likely to fall below 10°C. Do not apply as a traffic surface as too soft.

TECHNICAL DATA:

Resin:	Acrylic co-polymer
Solvent:	Water
Finish:	Low Sheen (5-7% @ 60°)
Colour:	White/Limited Colours
Touch Dry (minimum):	60 minutes @ 20°C
Recoat Time (minimum):	2-4 hours
Primer:	See over
Number of Coats:	2
Dry Film Thickness:	
Wet Film Thickness:	
Durability:	Very good
Thinning and Clean Up:	Water
VOC:	
Pot Life:	Not Applicable
Pack Size:	1, 4, 10 Litre

SPREAD RATE:

Theoretical Coverage: 10-12 m²/litre/coat.
Coverage depends on surface profile and porosity.

COMPUTER CODES:

EVO Acrylic Low Sheen White 01-225

Coating Technologies Limited, 16 Aetna Place, Henderson, Auckland, New Zealand

Phone: 0064 9 837 0897 Fax: 0064 9 837 3736 www.cotec.co.nz

Technical information given verbally or in writing is based on knowledge and research, given in good faith and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all merchandise is sold and received subject to the condition that our liability whether express or implied for any defect in quality, or for any lack of fitness for the specified use thereof, is limited to the return of the purchase price if written claim is made within 14 days from the date of delivery. It is recommended that the user makes his or her own tests to determine the suitability of the product for his own requirements. Freedom from patent restrictions is not implied.

EVO ACRYLIC LOW SHEEN

SURFACE PREPARATION:

(Refer to “Surface Preparation and Paint Systems” for full details). To ensure a successful application all surfaces to be coated must be clean, dry and stable.

All cracks and joints need to be treated as appropriate to suit the situation. Do not expect paint to bridge moving cracks/joints successfully.

Any mould, moss or algae needs to be treated with a suitable chemical cleaner/inhibitor.

Ensure surfaces are free from oil, grease and any surface contamination. Use commercial detergent/alkali cleaner, not acid wash.

Note: Commencement of work on a surface means in general you accept that surface. If any doubt about condition etc, seek advise.

GIB BOARD, PLASTERBOARD ETC, NEW:

Ensure all fixing, jointing and flushing is done to manufacturers specification. Repair any damaged areas with suitable plaster. Allow to cure. All surfaces must be clean and free of dust, dirt, grease etc.

Use ACRYLIC SEALER UNDERCOAT, or EVO EASYSAND for best finish. Sand to an acceptable finish. See their data sheets.

ALL PAINTED SURFACES:

Remove any and all flaking or blistering paint by chemical, mechanical means. Be careful not to create an undue profile or damage the underlying substrate. Repair any damaged areas with suitable plaster/filler. Allow to cure. All surfaces must be clean and free of dust, dirt, grease etc. Check soundness of existing paint film by cross-cutting with a sharp blade and applying tape. Rip off tape. If paint comes away surface is unsound and stripping is required prior to repainting.

Use of ACRYLIC SEALER UNDERCOAT, or EVO EASYSAND recommended.

No primer is required if previously painted surfaces in good condition and not flaking, blistering.

WOOD:

Generally requires a primer to fill and seal the surface. An oil based primer (ALKYD WOOD PRIMER) or water based primer (EVO EASYSAND), can be used.

Staining can result from the sap of some timbers.

APPLICATION:

Brush and Roller: Use product as is. Roller (6-8 mm good quality),

Spray: Not recommended.

THINNING & CLEAN UP:

Maximum thinning 10%. Clean up in water. Use a small amount of detergent to aid clean up.

ENVIRONMENTAL:

The evolution (EVO) range of products are formulated on the latest available resins to give you both high performance and also to meet low VOC (Volatile Organic Compound) levels set out in current local standards. Likewise levels of environmentally harmful substances are either significantly reduced or eliminated. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET.
