



High Performance Paint Product Data Sheet



DIAMOND HARDENER

56-4000 JUN 09



DESCRIPTION: An easy stir-in additive for TUFF FLOOR PUD CLEAR, to further enhance chemical and mechanical resistance properties for high wear areas.

TYPICAL USES: Areas with high traffic or wear, such as homes, restaurants, shops and other public areas.
Can also be used to improve the adhesion of single pack clears such as TUFF FLOOR PUD when repainting existing clear coatings.

PERFORMANCE: Provides the ultimate in durability properties when added to TUFF FLOOR PUD CLEAR.

LIMITATIONS: Not applicable.

TECHNICAL DATA:

Resin:

Solvent:

Finish:

Colour: Clear

Touch Dry (minimum):

Recoat Time (minimum):

Primer:

Number of Coats:

Dry Film Thickness:

Wet Film Thickness:

Durability:

Thinning and Clean Up:

VOC:

Pot Life: 4 hours @ 20°C (when mixed with TUFF FLOOR PUD CLEAR)

Mixing Ratio: 10:1 by volume

Pack Size: 100ml, 400ml, 1 Litre

SPREAD RATE:

Not applicable

COMPUTER CODES:

Tuff Floor Diamond Hardener 56-4000

Coating Technologies Limited, 16 Aetna Place, Henderson, Auckland, New Zealand

Phone: 0064 9 837 0897 Fax: 0064 9 837 3736 www.cotec.co.nz

Technical information given verbally or in writing is based on knowledge and research, given in good faith and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all merchandise is sold and received subject to the condition that our liability whether express or implied for any defect in quality, or for any lack of fitness for the specified use thereof, is limited to the return of the purchase price if written claim is made within 14 days from the date of delivery. It is recommended that the user makes his or her own tests to determine the suitability of the product for his own requirements. Freedom from patent restrictions is not implied.

DIAMOND HARDENER

SURFACE PREPARATION:

Not applicable.

APPLICATION:

Add DIAMOND HARDENER to TUFF FLOOR PUD CLEAR at the correct mix ratio, whilst stirring with a flat paddle. Continue to stir for 2 minutes, and then allow to stand for 5 minutes before use.

REFER TO THE TUFF FLOOR PUD CLEAR DATA SHEET FOR APPLICATION INSTRUCTIONS.

THINNING & CLEAN UP:

Not applicable.

ENVIRONMENTAL:

This formulation uses the latest technology with low toxicity, ensuring environmental issues are not compromised. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET.
