



High Performance Paint Product Data Sheet



DE-TAG GEL

96-200 AUG 09



DESCRIPTION: DE-TAG GEL is a low-environmental impact water soluble graffiti remover, which incorporates natural citrus oils. It is designed to eradicate common graffiti mediums such as permanent marker and enamel or acrylic aerosol spray paint from surfaces which have previously been protected with 2K ANTI-GRAFFITI CLEAR.

TYPICAL USES: Any surface coated with 2K ANTI-GRAFFITI CLEAR, where graffiti is a problem - including concrete, steel, timber and painted surfaces.

PERFORMANCE: When applied to a surface previously coated with 2K ANTI-GRAFFITI CLEAR, will allow easy removal of common graffiti mediums such as enamel and acrylic spray paint, ballpoint and marker pens.

LIMITATIONS: Graffiti should be removed as quickly as possible to maximise effectiveness. Some permanent markers may leave a "ghost" image. Only apply over surfaces previously coated with 2K ANTI-GRAFFITI CLEAR. Application to other paint coatings may strip the underlying coating. Product may react with plastics or vinyl's. If you have concerns regarding possible reactions between this product and other materials, please contact CTL's Technical Department.

2K ANTI-GRAFFITI CLEAR SHOULD BE ALLOWED TO CURE FOR AT LEAST A WEEK BEFORE APPLICATION OF DE-TAG GEL.

TECHNICAL DATA:

Resin:	Not Applicable
Solvent:	Not Applicable
Finish:	Not Applicable
Colour:	Clear Gel
Touch Dry (minimum):	Should be washed off within 30 minutes
Recoat Time (minimum):	Not Applicable
Primer:	Not Applicable
Number of Coats:	Not Applicable
Dry Film Thickness:	Not Applicable
Wet Film Thickness:	Not Applicable
Durability:	Not Applicable
Thinning and Clean Up:	Water
VOC:	
Pot Life:	Not Applicable
Pack Size:	4 Litre

SPREAD RATE:

Apply gel liberally by brush to affected area.

COMPUTER CODES:

De-Tag Gel	96-200
------------	--------

Coating Technologies Limited, 16 Aetna Place, Henderson, Auckland, New Zealand

Phone: 0064 9 837 0897 Fax: 0064 9 837 3736 www.cotec.co.nz

Technical information given verbally or in writing is based on knowledge and research, given in good faith and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all merchandise is sold and received subject to the condition that our liability whether express or implied for any defect in quality, or for any lack of fitness for the specified use thereof, is limited to the return of the purchase price if written claim is made within 14 days from the date of delivery. It is recommended that the user makes his or her own tests to determine the suitability of the product for his own requirements. Freedom from patent restrictions is not implied.

DE-TAG GEL

SURFACE PREPARATION/APPLICATION:

DE-TAG GEL is designed to facilitate removal of graffiti mediums such as enamel or acrylic aerosol spray paint, permanent marker, ballpoint pen etc from surfaces previously coated with 2K ANTI-GRAFFITI CLEAR.

Product should be applied liberally to the affected area by brush, and left for 10-15 minutes. Graffiti may then be removed by scrubbing with a rough cloth, nylon brush or by water blasting. Residue is then washed away with water. More stubborn graffiti may require a repeat application.

Do not use abrasive mediums to clean graffiti, as this will scour the protective coating, causing further graffiti to adhere more firmly.

Do not apply DE-TAG GEL to surfaces coated with standard coatings, as the product may strip the underlying coating. Product may also have a damaging effect on plastic or vinyl surfaces.

Note: DE-TAG GEL should be washed off within 30 minutes. Reseal lid after use to avoid evaporation.

2K ANTI-GRAFFITI CLEAR SHOULD BE ALLOWED TO CURE FOR AT LEAST A WEEK BEFORE APPLICATION OF DE-TAG GEL.

WHEN APPLYING THIS PRODUCT, ALWAYS WEAR SAFETY GLASSES AND PROTECTIVE GLOVES/CLOTHING (refer to material safety data sheet).

THINNING & CLEAN UP:

Thinning is not usually required. Use water and detergent for clean-up.

ENVIRONMENTAL:

DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET.
